1000R



HIGHLIGHTS

- Rotax® snorkeled V-Twin engine with relocated CVT intake and outlet
- Intelligent Throttle Control (iTC™) with riding modes
- Front and rear FOX[†] 1.5 PODIUM[†] QS3
- 30 in. ITP† Cryptid† tires
- 14 in. cast-aluminum beadlock wheels
- 3,500 lb (1,588 kg) winch
- · Front and central aluminum skid plate
- Heavy-duty front and rear bumpers
- · Aluminum taper-profile handlebar with grab handle and full-wrap handguards
- Tri-Mode Dynamic Power Steering (DPS™)
- · Continuously Variable Transmission (CVT) with extra-low L-gear
- Torsional Trailing-Arm Independent (TTI) rear suspension
- Mudguards
- Multifunction digital gauge
- · Painted plastics for premium look
- · X-package coloration, graphics and seat cover

SPECIFIC TO VISCO-4LOK PACKAGE

• NEW Visco-4Lok front differential



Neo Yellow & Black / 1000R (with Visco-4Lok)
Iron Gray & Manta Green / 1000R

DIMENSIONS &

ENGINE	1000R with Visco-4Lok	1000R	
Туре		91 hp, Rotax 976 cc V-twin, snorkeled liquid cooled with relocated radiator	
Fuel Delivery System		Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)	
Transmission	CVT, P/R/N/H/extra-low L	CVT, P/R/N/H/extra-low L, standard engine braking	
Drive Train	Selectable 2WD/4WD/ Lock 4WD with Visco-4Lok front differential	Selectable 2WD/4WD with Visco-Lok† QE auto- locking front differential	
Power Steering	Tri-Mode Dynamic P	Tri-Mode Dynamic Power Steering (DPS)	
SUSPENSIONS			
Front Suspension	Arched double A-arm with front sway bar		
Front Shocks	FOX 1.5 PC	FOX 1.5 PODIUM QS3	
Rear Suspension	Torsional Trailing-Ar	Torsional Trailing-Arm Independent (TTI)	
Rear Shocks	FOX 1.5 PC	FOX 1.5 PODIUM QS3	
TIRES & WHEELS			
Front Tires	ITP Cryptid 30 x 9 x 14 ir	n. (76.2 x 22.9 x 35.6 cm)	
Rear Tires	ITP Cryptid 30 x 9 x 14 ir	n. (76.2 x 22.9 x 35.6 cm)	
Wheels	14 in. cast-alum	ninum beadlock	
BRAKES			
Front		Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	
Rear		ntilated disc brake vin-piston caliper	

CAPACITIES	with Visco-4Lok	
Estimated Dry Weight*	991 lb (450 kg)	
LxWxH	83 x 50 x 56 in. (224 x 127 x 131 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	12 .5 in. (31.8 cm)	
Seat Height	36.75 in. (93.3 cm)	
Rack Capacity	Rear: 35 lb (16 kg)	
Storage Capacity	N/A	
Towing Capacity	1,300 lb (590 kg)	
Fuel Capacity	5.4 gal (20.5 L)	
FEATURES		
Gauge	4.5 in. digital display: Speedometer, tachometer, odometer, trip and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock	
Instrumentation	Lighter type DC outlet in console, standard connector in the back (15 A)	

1000R

	odometer, trip and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock
Instrumentation	Lighter type DC outlet in console, standard connector in the back (15 A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light/brake light
Winch	3,500 lb (1,588 kg) winch
Seat	Standard
Protection	Front and rear bumpers Aluminum taper-profile handlebar with grab handle and full-wrap handguards Mudguards Front and central aluminum skid plate

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months

